



## FRICITION LOSS CHART

Permissible ranges of volume rates of flow in l/s through Galvanized Steel Pipe to limit Friction Losses to 10 Percent of the Pipe Length.

Grade →	Light	Medium	Heavy
Nominal pipe dia in mm ↓	Rate of flow in lps	Rate of flow in lps	Rate of flow in lps
40	1.90 - 2.74	1.79 - 2.67	1.59 - 2.41
50	2.74 - 5.24	2.67 - 4.95	2.41 - 4.54
65	5.24 - 9.97	4.95 - 9.80	4.54 - 9.17
80	9.97 - 15.54	9.80 - 14.97	9.17 - 14.20
100	15.54 - 30.84	14.97 - 30.0	14.20 - 28.67
125	-	30.0 - 52.50	28.67 - 51.37
150	-	52.50 - 84.18	51.37 - 82.63

Permissible ranges of volume rates of flow in l/s through RPVC Pipe to limit Friction Losses to 10 Percent of the Pipe Length.

Grade →	Class (0.25Mpa)	Class (0.4Mpa)	Class (0.6Mpa)
Nominal pipe dia in mm ↓	Rate of flow in lps	Rate of flow in lps	Rate of flow in lps
40	-	-	Up to 2.04
50	-	-	2.04 - 3.70
63	-	3.80 - 7.24	3.70 - 6.77
75	-	7.24 - 11.47	6.77 - 10.76
90	11.50 - 19.58	11.47 - 18.50	10.76 - 17.41
110	19.58 - 33.25	18.59 - 31.71	17.41 - 29.75
125	33.25 - 46.63	31.71 - 44.33	29.75 - 41.44
140	46.63 - 62.92	44.33 - 59.79	41.44 - 55.97
160	62.92 - 89.28	59.79 - 84.95	55.97 - 79.76



## FRICITION LOSS CHART

Friction loss in metres for 10 metres long new RPVC pipe (C= 150)

Nominal Pipe Outer dia in mm / inches	40/ 1½"	50/ 2"	63/ 2½"	75/ 3"	90/ 3½"	110/ 4¼"	125/ 5"	140/ 5½"	160/ 6¼"
	Volume rate of flow lps								
0.50	0.074								
1.00	0.268								
1.25	0.405	0.131							
1.60	0.640	0.211							
2.00	0.967	0.310							
2.50	1.462	0.483	0.150						
3.20	2.309	0.762	0.250	0.106					
4.0	3.491	1.153	0.377	0.160					
5.0		1.742	0.571	0.242					
8.0		4.161	1.363	0.577	0.237				
10.0			2.060	0.873	0.358	0.133			
12.5			3.114	1.319	0.542	0.201			
16			4.919	2.084	0.856	0.317	0.172		
20				3.151	1.293	0.479	0.260		
25					1.955	0.725	0.392	0.225	0.117
32					3.089	1.145	0.020	0.355	0.184
40						1.731	0.937	0.537	0.279
50						2.617	1.416	0.812	0.421
60						3.008	1.985	1.138	0.590
80							3.382	1.939	1.006
100								2.931	1.521
125									2.299



## FRICITION LOSS CHART

Friction loss in metres for 10 metres long new steel galvanized pipe (C=40)

Nominal Pipe Outer dia in mm / inches	25/ 1"	32/ 1¼"	40/ 1½"	50/ 2"	65/ 2½"	80/ 3"	100/ 4"	125/ 5"	150/ 6"
	Volume rate of flow lps								
0.50	0.364								
1.00	1.315	0.341							
1.25	1.988	0.516	0.246						
1.60	3.140	0.814	0.388						
2.00		1.231	0.587						
2.50		1.861	0.888	0.282					
3.2		2.940	1.402	0.446	0.126				
4.0			2.120	0.674	0.190				
5.0			3.205	1.019	0.288				
8.0				2.433	0.887	0.313			
10.0				3.678	1.038	0.474	0.131		
12.5					1.570	0.716	0.198		
16					2.479	1.131	0.312	0.111	
20					3.747	1.710	0.472	0.167	
25						2.585	0.713	0.253	0.106
32						4.033	1.127	0.400	0.157
40							1.704	0.605	0.252
50							2.576	0.914	0.351
60								1.281	0.534
80								0.182	0.910
100								3.299	1.376
125									0.051